

AVU50S82 Service temperature wine cellar Built-under counter range







Our products are manufactured in compliance with European environmental rules. Especially, refrigerant fluid (R600a) doesn't reject neither CFC nor HFC and respect environment.

Energy consumption is calculated based on the result obtained for 24h in standard test conditions. The actual energy consumption depends on the conditions of use and location of the device.

This equipment is designed to be used in an ambient temperature between 10°-39°C

This appliance is intended to be used exclusively for the storage of wine.

Alcohol abuse is dangerous for health, please consume in moderation.

*Capacity given as an indication with 75cl Bordeaux traditional type bottles and measured with 4 shelves. Adding shelves reduce considerably the total capacity.

capacity.

**Thanks to the Vinotag® application, benefit from a digital register of your wine cellar and be alerted of the peak dates of your wines. In partnership with Vivino, scan your bottle to access its pre-filled wine sheet.

- Capacity: 44 bottles*
- + Vinotag compatible**
- Free standing and built-under counter installation
- Design: black body & black piano organic glass door frame
- Cooling system: compressor
- Type of cold: air moving system
- Adjustable temperature range of use: 5°C-20°C
- Electronic regulation
- Thermometer with white electronic display
- White LED lights with switch button
- Humidity control: water tray
- 1 reversible glass door, anti-UV treated, 3-layers tempered glass (grey-colored)

Its wooden shelves on telescopic rails facilitate access to the bottles.

With **door and temperature alarms**, offer the best protection to your wine bottles.

A **discreet handle** under the worktop to blend seamlessly into any kitchen.

A 2 cm **recess plinth** for perfect alignment.

A **removable plinth** to pass any perforated kitchen plinth. (Total of 7.5 cm)

A **plumbing passage** at the back so that no space is lost in the product recess.

Reversibility possible for door opening.



AVU50S82 Service temperature wine cellar Built-under counter range



> EQUIPMENTS INCLUDED

- 4 sliding wooden shelves (beech)
- 1 fixed wooden presentation shelf
- 4 adjustable feet (height 7 cm)
- Plumbing passage
- Anti-vibration system
- Removable ventilation grid

> TECHNICAL CHARACTERISTICS

■ Energy class: F

■ Annual electrical consumption: 105 kWh

Climatic class: SN-STNoise level: 38 dB

■ EEI: 123.90

Voltage: 220-240 VPower input: 80 WCategory: 2 - Wine cellar

■ Type of gas: R600a

> SAFETY

Visual and audible alarms: notify you when your attention is required

> VINOTAG® APPLICATION

Free wine cellar management application. Access a virtual representation of your wine cellar and a detailed inventory of its contents.

> COMPATIBLE ACCESSORIES

Only available in spare parts

> LOGISTIC DATAS

Gross dimensions (WxDxH cm) : $65 \times 61 \times 85$ Net dimensions (WxDxH cm) : $59,5 \times 57,4 \times 81,7$

Gross weight (kg) : 46.00

Net weight (kg) : 42.00

 Net weight (kg)
 : 42.0

 Full truck (pcs)
 : 0

 Container (pcs)
 20' : 0

 40' : 0

40' HC : 170

Gencod 3595320108071

Non-contractual pictures Last update: 20/05/2024